## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	sources					
Supplier's name or trade mark: Lumina Italia srl						
Supplier's address: Lumina Italia srl, Via Casorezzo 63, 20010 Arluno Milano, IT						
Model identifier: Daphine led / Daphinette led						
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		solded cables				
(or other electri	ic interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		11	Energy efficiency class	E		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 287 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), expressed in W		11,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	97		
Outer dimen-	Height	28	Spectral power dis-	See image		
sions without	Width	50	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	77	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,433			
		nates (x and y)	0,403			
Parameters for directional light sources:						
Peak luminous intensity (cd)	487	Beam angle in degrees, or the range of beam angles that can be set	118			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	90	Survival factor	-			
the lumen maintenance factor	0,97					

(a)'-': not applicable; (b)'-': not applicable;

