

## COASSIALE

code: **2885/S/NE**






DESIGN VITTORIO VENEZIA 2017



DIRECT AND INDIRECT LIGHT, THANKS TO THE LED LIGHT SOURCES HOLD INSIDE TWO COLORED ALUMINIUM CYLINDRICAL SUPPORTS WHICH ARE AT THE ENDPOINT OF THE TWICE POWER CABLES. ONE IS FOR THE CEILING CONNECTION, THE OTHER ONE IS USED AS A COUNTER-WEIGHT. THE LIGHT IS REFLECTED ON A SWIVEL DISK IN A WHITE OPAL METHACRYLATE MATERIAL WHICH SPACES AND SLIDES ALONG TWO CABLES, TO CREATE DIFFERENT LIGHT EFFECTS. INFERIOR CYLINDRICAL SUPPORT WITH A CABLE AND AN ELECTRONIC DRIVER ON THE PLUG.

### TECHNICAL DRAWINGS



<b>UTILIZATION:</b>	<b>INTERNAL</b>	<b>TYPOLGY:</b>	<b>CEILING LAMPS</b>	
<b>COLOURS</b>	STRUCTURE: DIFFUSER:	<b>BLACK</b> <b>WHITE</b>		
<b>MATERIALS</b>	STRUCTURE: DIFFUSER:	<b>ALUMINIUM</b> <b>OPAL WHITE METHACRYLATE</b>		
<b>MEASURES</b>	WIDTH: - HEIGHT: <b>250 cm</b> LENGTH: - DEPTH: -  PACKAGING VOL.M <sup>3</sup> : -	DIAMETER: <b>35 cm</b> HOLE DIAMETER: - HOLE DEPTH: -	WEIGHT NET: <b>2</b> GROSS: -	NUMBER OF ITEMS: -
<b>BULBS</b>	LED 1X20W FLUX: 2200LM KELVIN: 3000° CLASS: A++ CRI: >80 COLOR TOLERANCE: - DURATION: 40000H			
<b>DEVICE SPECIFICATIONS</b>	TYPE OF EMISSION: - POWER: - FLOW LAMP: - BEAM ANGLE: - DEVICE EFFICIENCY: <b>-lm/W</b> IMPACT RESISTANCE: - GLOW WIRE TEST: -		POWER SUPPLY CABLE LENGTH: - LENGTH OF HANGING CABLE: - SUPPLY: <b>INCLUDED</b> POWER SUPPLY ASSEMBLY: <b>EXTERNAL</b> TYPE OF DIMMING: - VOLTAGE: <b>230 V</b>	
	POWER SUPPLY: <b>ELECTRONIC DRIVER WITH CABLE AND PLUG</b>			
<b>CERTIFICATIONS</b>	   			
<b>MARKETS</b>	THIS ITEM IS AVAILABLE IN THE FOLLOWING COUNTRIES: <b>EUROPE</b>			