

FORTEBRACCIO

design Alberto Meda / Paolo Rizzato, 1998

**LUCE
PLAN**

Type: Wall or ceiling/wall


| | | | |
|---------------|------------|-------------------------------|--------|
| Light source: | D33Nsp.60 | 28W Spot R50 E14 energy saver | EEL: D |
| | | 42W HSGSA E14 energy saver | EEL: D |
| | | LED 6W E14 | EEL: A |
| | D33Nsp.100 | 42W Spot R63 E27 energy saver | EEL: D |
| | | 70W HSGSA E27 energy saver | EEL: D |
| | | LED 9 W E27 | EEL: A |
| | D33N.100 | 70W HSGSA E27 energy saver | EEL: D |
| | | LED 9W E27 | EEL: A |
| | D33N.100 D | 70W HSGSA E27 energy saver | EEL: D |
| | Dimmable | LED 9W E27 | EEL: A |

Product use: Indoor

Materials: Injection-moulded grip /moulded polycarbonate sheared and formed steel arms, die-cast metal joints

Colors: white, black soft touch, metal

Description: The central joint allows the two arms to rotate independently on the horizontal and vertical axis, guaranteeing great fluidity of movement even in extreme and unusual positioning. The polycarbonate grip enables users to maneuver the lamp simply and manageably.


Insulation class: 

Awards: Compasso d'Oro ADI 2001, selection


| | | |
|-----------------|-------------|---|
| Reference code: | Structure | |
| | D33N.100 | 1D33N2GI0002 white 1D33N2GI0001 black soft touch 1D33N2GI00AA metal |
| | D33N.100D | 1D33N2GD0002 white 1D33N2GD00AA metal |
| | D33Nsp. 60 | 1D33NSPI0002 white 1D33NSPI00AA metal 1D33NSPI0001 black soft touch |
| | D33Nsp. 100 | 1D33NSGI0002 white 1D33NSGI00AA metal 1D33NSGI0001 black soft touch |
| | Component | |
| | D33N/3 | 1D33N/03000A universal joint metal |




D33 N.100 - D33N.100D



D33Nsp.60



D33 Nsp. 100



D33N/3
universal joint

